

US-1326/ Batería Lithium Lithium battery

		Tiempo de carga Charging time	Peso Weight
US-1326/1.5	20 V. 1.5 Ah	60 min (aprox)	0,4 Kg
US-1326/2.0	20 V. 2.0 Ah	68 min (aprox)	0,5 Kg
US-1326/4.0	20 V. 4.0 Ah	160 min (aprox)	0,7 Kg



Indicador nivel de batería - Battery level indicator

US-1326/C Cargador baterías Battery charger


Cargador rápido, inteligente, con led indicador
Intelligent, fast charger with LED indicator

US-1352 Taladro a batería 12V - 12V Cordless drill



Par de apriete	Max. torque	2,04 Kg-m / 20 NMm / 14.4 ft-lb
Par de ajuste	Thghtening torque	17+1
Selector de velocidad	Speed knob	Alta - High: 1350 rpm Baja - Low: 400 rpm
Capacidad porta-brocas	Chuck capacity	10 mm
Tiempo de carga	Charging time	3-5 h
Batería	Battery	12 V/1,3 Ah Li-ion
Tensión cargador	Charger voltage	100-240 VAC, 50/60 Hz
Peso llave	Tool weight	0,98 Kg
Peso estuche	Case weight	3 Kg
Medidas estuche	Case dimensions	350 × 280 × 110 mm



Dotación:

- 24 Puntas 1/4" 25mm - 24 1/4" 25mm Bits SL: 4-5,5-7 - PH: 1-2-3-4 - PZ: 1-2-3-4 - T: 8 - H: 4-5-6-7-8 - T: 10-15-20-25-27-30-40
- 1 Mango destornillador 1/4" - 1/4" Ratchet screwdriver • 5 Brocas de madera - Wood working drill bits 3-4-5-6-8mm
- 2 Brocas reductoras de 1/4" 75 mm 1/4" 75mm redicing shank bits SL 4 - PH 1
- 3 Brocas de pala para madera - Wood flat drill bits 13-16-19mm • 4 Puntas 1/4" 50mm - 1/4" 50mm bits PH 2-, SL 5-6
- 8 Brocas HSS - Twist drill bits 1,5-2-2,5-3-4-5-6-8mm • 8 Vasos de 38mm destornillador - Socket 4-5-6-8-10-11-12-13mm
- 1 Flexómetro de - Measuring tape 3 m • 1 Soporte magnético - Magnetic holder 63 mm • 1 Taladro - Power tool set 12 V

US-1355 Taladro con percutor y atornillador a batería 20V 20V Cordless Drill / Driver



2 2.0Am batteries

Dotación:

- 1 Taladro 60mm
- 6 Brocas HSS 2-2,5-3-4-5-6mm
- 6 Punta 25mm SL: 5-6 / PH: 1-2 / PZ: 1-2

Accessories:

- 1 CRV 60mm Holder
- 6 HSS Twist drill bits 2-2,5-3-4-5-6mm
- 6 Screwdriver bit set 25mm SL: 5-6 / PH: 1-2 / PZ: 1-2

Par de apriete	Max. torque	4,08 Kg-m / 45 NMm / 29.5 ft-lb
Par de ajuste	Thghtening torque	20 +1 + 1
Selector de velocidad	Speed knob	Alta - High: 1800 rpm Baja - Low: 500 rpm
Capacidad porta-brocas	Chuck capacity	13 mm
Tasa de impacto	Impact rate	0-8500/0-30600bpm
Tiempo de carga	Charging time	1 h
Batería	Battery	2x2000 mAh Li-ion
Peso llave	Tool weight	1,8 Kg
Peso estuche	Case weight	3,9 Kg
Medidas estuche	Case dimensions	350 × 320 × 100 mm