

Bobinas
Welding wire



Art		Ø	Kg
JAR-2473	Cu/Si	0,8 mm	5
JAR-2473/1	Cu/Si	0,8 mm	1
JAR-2473/2	Cu/Si	0,8 mm	2
JAR-2474	Cu/Al	0,8 mm	3
JAR-2475	SG-2	0,6 mm	5
JAR-2477	SG-2	0,8 mm	5
JAR-2477/1	SG-2	0,8 mm	1
JAR-2477/15	SG-2	0,8 mm	15

Art		Ø	Kg
JAR-2478	SG-2	1 mm	5
JAR-2478/15	SG-2	1 mm	15
JAR-2479/15	SG-2	1,2 mm	15
JAR-2482/0,5	Al/Mg	1 mm	0,5
JAR-2482/2	Al/Mg	1 mm	2
JAR-2483/0,5	Al/Si	1 mm	0,5
JAR-2483/2	Al/Si	1 mm	2
JAR-2484	308	1 mm	5
JAR-2484/3	308	1 mm	3

Art		Ø	Kg
JAR-2480	Tubular Sin Gas Without Gas	0,9 mm	5
JAR-2480/0,5	Tubular Sin Gas Without Gas	0,9 mm	0,5

JAR-2980
Kit Pantalla Protección + Soporte
Protective Screen + Spport Kit



Kit compuesto por una pantalla de protección de color rojo con soporte autoportante pensado para la protección y la división de las áreas de elaboración dedicadas a soldadura, esmerilado o cuando sea necesario proteger ante chispas y salpicaduras. La pantalla está realizada con PVC de alta resistencia al calor y chispas (hasta 300°C) y tiene unas dimensiones de 1740x1740 mm. El soporte tiene unas dimensiones de 670x1790x1960 mm y está provisto de 4 ruedas giratorias para un desplazamiento ágil. Equipo de protección conforme con las normas DIN EN 1598:2011-12 y DIN EN ISO 15980:2014. Peso 7,8 Kg

Red protective screen and self-support kit, designed to protect and separate work areas dedicated to welding, grinding or wherever protection is needed against sparks and sprays. The screen is made of PVC with high resistances to heat and sparks (up to 300°C) and measures 1740x1740 mm. The support measures 670x1790x1960 mm and is equipped with 4 swivel wheels for agile movement. Protective equipment conforming to standards DIN EN 1598:2011-12 and DIN EN ISO 15980:2014

JAR-2980/R
Pantalla de Protección Roja 1740x1740 mm
Red Protective Screen 1740x1740 mm



Mantas de protección
Protective blanket



Art.	Resistencia al calor Heat resistance	Material	Color	Tamaño Size	Dimensiones Dimensions	Peso Weight
JAR-2981/A	550 °C (*)	E-glass fiberglass fabric	Blanco White	0,8 mm +/-15%	1950x2000 +/- 5% mm	3,64 Kg
JAR-2981/B	1100 °C	Ceramic Fiber	Blanco White	1,5mm +/-10%	1500 x 1900 +/-5% mm	3,10 Kg
JAR-2981/C	1300 °C	Carbonized Fiber	Negro Black	3,5mm - 5mm	1800 x 2000 +/-5% mm	2,42 Kg