

**US-1168**

**Lámpara COB LED modelo "I-VIEW" Lamp**


Fuente luz - Light source	COB LED
Lumen - Luminous flux	125-250
Illuminance, lux@0,5 m	400-600
Adjustable light output	2 levels
Beam angle	120°/60°
CRI	VRa> 80
CCT	6000K
Operating time	Up to 5 h
Charging time	3 h
Battery	3,8V/1600 mAh Li-on
Protection class	IP65/IK07
Impact resistance	1 m
Cable	1m USB
Charging voltage current DC	5V / 1A
Power consumption	Max 3 W
Temperature	-10° to +40°C
Dimensions	105x52x43 mm
Peso neto - Net weight	0,260 Kg



**US -1204**

**Lámpara COB LED "MINI SLIM" Lamp**

Fuente luz - Light source	COB LED
Spot: High power LED	
Lumen - Luminous flux	100-200 Spot: 100
Illuminance, lux@0,5 m	150-400 Spot: 5200
Adjustable light output	2 levels
CRI	Ra> 80
CCT	6000K
Operating time	Up to 5 h
Charging time	4,5 h
Battery	3,8V/2800 mAh Li-on
Protection class	IP30
Impact resistance	1 m
Cable	1m USB
Charging voltage current DC	5V / 1A
Power consumption	Max 4 W
Temperature	-10° to +40°C
Dimensions	165x44x28 mm
Peso neto - Net weight	0,224 Kg



**US-1205**

**Lámpara COB LED "STAR" Lamp**

Fuente luz - Light source	COB LED
Lumen - Luminous flux	500-1000
Illuminance, lux@0,5 m	800-1600
Adjustable light output	2 levels
CRI	Ra> 80
CCT	6000K
Operating time	Up to 5 h
Charging time	6 h
Battery	3,7V/5200 mAh Li-on
Protection class	IP65
Impact resistance	1m USB
Cable	1m USB
Charging voltage current DC	5V / 1A
Power consumption	Max 8,5 W
Temperature	-10° to +40°C
Dimensions	156x103x98 mm
• Peso neto - Net weight	0,710 Kg




**US-1284**

**Lámpara COB LED "SOUNDLED S" Lamp**

Luz de trabajo pequeña y compacta con altavoz integrado  
Small and compact work light with integrated speaker

Fuente luz - Light source	COB LED
Lumen - Luminous flux	300-600
Illuminance, lux@0,5 m	1000-2000
Adjustable light output	2 levels
Beam angle	60°
CCT	6000K
Operating time	6 h
Charging time	5 h
Battery	3,7V/5200 mAh Li-on
Protection class	IP65/IK07
Impact resistance	1m USB mini DC
Cable	1m USB
Charging voltage current DC	5V / 2A
Power consumption	7 W
Temperature	-10° to +40°C
Dimensions	92x86x74 mm
• Peso neto - Net weight	0,430 Kg



**Lámpara modelo "NOVA" luz fría COB LED Lamp**



Art.	<b>US-1048 NOVA 30</b>	<b>US-1133 NOVA 20</b>	<b>US-1207 NOVA 5</b>
Fuente luz - Light source	30W High CRI COB LED	20W High CRI COB LED	High efficiency COB LED
Lumen - Luminous flux	3300	2000	500-5000
Illuminance, lux@0,5 m	5000	4000	800-8000
Adjustable light output	-	-	5 levels
CRI	Ra> 80	Ra> 80	Ra> 80
CCT	6000K	6000K	6000K
Protection class	IP67/IK07	IP67/IK07	IP67/IK07V
Cable	5m/3x1mm²H05RN-F	5m/3x1mm²H05RN-F	5m/3x1mm²H05RN-F
Operating voltage AC	100-240V 50/60Hz	100-240V 50/60Hz	100-240V 50/60Hz
Power consumption	30 W	20 W	Max 42 W
Temperature	-10° to +40°C	-10° to +40°C	-10° to +40°C
Dimensions	261x274x76mm	220x235x75mm	267x262x87mm
• Peso neto - Net weight	2,8 Kg	2 Kg	2,6 Kg

