

US-996

Portátil recargable de 60 leds

60 Leds portable rechargeable light

Portátil de 60 Leds recargable, con cargadores de corriente 230 V. Con gancho para sujeción fácil. Luminosidad 550 Lux. Autonomía entre 3 y 4 horas. Tiempo de carga máxima 2 horas

60 leds portable rechargeable light, with current charger, hook for an easy suspension 550 Lux. brightness. Autonomy between 3 and 4 hours. Charger time max. 2 hours.

• Peso - Weight: 0,720 Kg



US-1080

Portátil recargable "LINE LIGHT R" Portable lamp

Fuente luz - Light source	36 SMD LED 1 x CREE XP-G2 in top
Lumen - Luminous flux	80 / 220
Illuminance, lux@0,5 m	600 / 800
Adjustable light output	-
Beam angle	50° - 75°
Operating time	4/6 h
Charging time	4 h
Battery	1 Li-Ion
Power consumption	2,5 W
Temperature	-10° to +40°C
Dimensions	50 x 10 x 10 mm
Peso neto - Net weight	0,500 Kg



US-1287

Juego de fluorescentes "LINE LIGHT 2-POST" Fluorescent kit

Fuente luz - Light source	2 x 6 SMD LED
Lumen - Luminous flux	2 x 600
Illuminance, lux@0,5 m	2 x 1300
Adjustable light output	stepless
Beam angle	75°
CRI	Ra > 80
CCT	6000K
Protection class	IP67/IK07
Cable	8 m /H03VV-F 2 x 0,5 mm ²
Charging voltage current DC	24V
Power consumption	Ma 2x9W
Temperature	-10° to +40°C
Dimensions	2 x Ø25 x 770 mm
Peso neto - Net weight	2,9 Kg



US-1288

Lámpara "SUPERFORM" Lamp

Fuente luz - Light source	COB LED
Lumen - Luminous flux	750
Illuminance, lux@0,5 m	1000
CRI	Ra > 80
CCT	6000K
Protection class	IP54 / IK08
Cable	5 m/H05RN-F 2x1 mm ²
Charging voltage current DC	100-240V
Power consumption	Max 8 W
Temperature	-10° to +40°C
Dimensions	270 x 49 x 31 mm
Peso neto - Net weight	0,710 Kg



US-551

Portátil fluorescente 230V

230V portable fluorescent

- Voltaje - Voltage 230V 8 W • Cable - Cable 200 OMS/m
- Temperatura máx. de trabajo - Max. temperature work 50° C
- Longitud del portátil - Portable length 500 mm
- Ø tubo exterior - External tube Ø 30 mm
- Longitud aprox. d cable - Approx. cable length 4,5 m
- Peso - Weight: 0,418 Kg



US-1167

Lámpara "STAR LITE" Lamp

Fuente luz - Light source	9 x SMD LG LED
Lumen - Luminous flux	300
Illuminance, lux@0,5 m	400
CRI	Ra > 80
CCT	6500K
Protection class	IP40 / IK08
Cable	5 m /2x1,0mm ² H05RN-F
Operating voltage AC	100-240V
Power consumption	Max 4 W
Temperature	-10° to +40°C
Dimensions	240x40x25 mm
Peso neto - Net weight	0,600 Kg



JAR-169

**Tubo fluorescente especial capós
Special fluorescent tube bonnets**

- Potencia - Power 21W
- Voltaje - Voltage 220-240 V Hz 50-60
- Longitud cable - Length cable 5000 mm
- Protección clase- Class protection II
- Grado - Degree Ip64
- Lm 2100
- Peso - Weight: 0,100 Kg



US-2

**Lámpara flexible con espejo articulado e imán
Flexible lamp with articulated mirror and magnet**

• Peso - Weight: 0,230 Kg



US-2/BIS

**Bombilla de recambio
Spare light bulb**

US-228

**Espejo telescópico y orientable
Telescopic and adjustable light**

• Peso - Weight: 0,050 Kg

