

US-1308
Lámpara LED 1W - 120 lm. Modelo Penlight
Penlight LED 1W 120 lm



Fuente luz - Light source	8 LED
Luz principal - Main light	120 lm
Luz superior- Top light	80 lm
Grado de protección - Protection class	IP29
Batería - Battery	3,7V/750 mAh Li-on
Cable	1m USB
Recarga máxima - Charging input	5V / 1A
Capacidad - Consumption	2,78 wh
Dimensiones - Dimensions	170x27x25 mm
Peso neto - Net weight	0,059 Kg

US-996
Portátil recargable de 60 leds
60 Leds portable rechargeable light

Portátil de 60 Leds recargable , con cargadores de corriente 230 V. Con gancho para sujeción fácil. Luminosidad 550 Lux. Autonomía entre 3 y 4 horas. Tiempo de carga máxima 2 horas
60 leds portable rechargeable light, with current charger, hook for an easy suspension 550 Lux. brightness. Autonomy between 3 and 4 hours.Charger time max. 2 hours.

- Peso - Weight: 0,720 Kg



US-551
Portátil fluorescente 230V
230V portable fluorescent

- Voltaje - Voltage 230V 8 W • Cable - Cable 200 OMS/m
- Temperatura máx. de trabajo - Max. temperature work 50° C
- Longitud del portátil - Portable length 500 mm
- Ø tubo exterior - External tube Ø 30 mm
- Longitud aprox. d cable - Approx. cable length 4,5 m
- Peso - Weight: 0,418 Kg



JAR-169/LED
Tubo fluorescente LED especial capós
Special LED fluorescent tube bonnets

- Potencia - Power 21W
- Voltaje - Voltage 220-240 V Hz 50-60
- Longitud cable - Length cable 5000 mm
- Protección clase- Class protection II
- Grado - Degree Ip64
- Lm 2100
- Peso - Weight: 0,100 Kg



US-2
Lampara flexible con espejo articulado e imán
Flexible lamp with articulated mirror and magnet

- Peso - Weight: 0,230 Kg



US-2/BIS
Bombilla de recambio
Spare light bulb

Lámpara modelo "NOVA" luz fría COB LED Lamp



Art.	US-1133 NOVA 20
Fuente luz - Light source	20W High CRI COB LED
Lumen - Luminous flux	2000
Iluminance, lux@0,5 m	4000
Adjustable light output	-
CRI	Ra> 80
CCT	6000K
Protection class	IP67/IK07
Cable	5m/3x1mm²H05RN-F
Operating voltage AC	100-240V 50/60Hz
Power consumption	20 W
Temperature	-10° to +40°C
Dimensions	220x235x75mm
• Peso neto - Net weight	2 Kg

