

Compresores de Pistón Estacionarios, bi Etapa a Correa Silenciosos Stationary Silents Piston's Compressors, Twin Stages Belt



Art.	CV-HP	r.p.m.	L/min	Bar	dB	Pistones por etapa Pistons per stage	Depósito Tank	Peso Weight	Fase Phase	Medidas Dimensions
COM-2630	5,5	1250	606	10	69	2 × 2	300	230 Kg	Triphase	1615 × 600 × 1264 mm
COM-2640	7,5	980	830	10	66	2 × 2	500	305 Kg	Triphase	2038 × 600 × 1357 mm
COM-2650	10	1050	910	10	66	2 × 2	500	310 Kg	Triphase	2038 × 600 × 1357 mm

Compresores de tornillo Screw Compressors



Art.	CV-HP	KW	L/min	Bar	dB	Salida Outlet	Depósito Tank	Peso Weight	Medidas Dimensions
COM-2860	10	7,5	1200 / 980 / 740	8 / 10 / 13	67	1/2"	500	260 Kg	2038 × 600 × 1367 mm
COM-2870	15	11	1560 / 1430 / 1210	8 / 10 / 13	67	3/4"	500	349 Kg	2038 × 600 × 1367 mm

Compresores de tornillo con tratamiento de aire - Screw compressors with air treatment

COM-2865	10	7,5	1200 / 980 / 740	8 / 10 / 13	67	1/2"	500	290 Kg	2038 × 600 × 1367 mm
COM-2875	15	11	1560 / 1430 / 1210	8 / 10 / 13	67	3/4"	500	380 Kg	2038 × 700 × 1446 mm
COM-2885	20	15	2010 / 1900 / 1210	8 / 10 / 13	67	3/4"	500	430 Kg	2038 × 700 × 1446 mm

Compresor portátil con motor a gasolina Portable compressor with gasoline engine

Compresor portátil con motor a gasolina para servicios en carretera y agrícolas. Arranque manual mediante tirador.
Portable compressor with gasoline engine for road and agricultural services. Manual starting by puller.



Art.	CV-HP	r.p.m.	L/min	Bar	Pistones por etapa Pistons per stage	Depósito Tank	Peso Weight	Medidas Dimensions
COM-2250	5,5	1170	540	10	2 × 2	11+11	85 Kg	820 × 700 × 790 mm

Secadores frigoríficos Refrigeration dryers

Art.	Caudal Flow	Volt	Conx	Pot	Peso Weight	Medidas Dimensions
COM-DD42	700 L/min 42 m³/h	220 M	3/4"	0,24 kW	23 Kg	305 × 373 × 440 mm
COM-DD60	1000 L/min 60 m³/h	220 M	3/4"	0,28 kW	24 Kg	305 × 373 × 440 mm
COM-DD90	1500 L/min 90 m³/h	220 M	3/4"	0,28 kW	25 Kg	345 × 409 × 480 mm

