

LOTE1

Composición:

1 x US-1324 - Taladro percutor sin cable 2 x 20V-1500mAh - Cordless "hammer" drill/driver

1 x US-2040 - Estuche de vasos y puntas conexión 1/4" [46 piezas] - Case of wrench sockets & bits, 1/4"

1 x US-1002/2 - Lámpara COB LED modelo "HEAD LITE" - Lamp COB LED "HEAD LITE"

US-1324

Taladro con percutor sin cable [20 V 1500 mAh]

Cordless "hammer" drill/driver [20 V 1500 mAh]



Par de apriete	Max. torque	3,26 Kg-m / 32 Nm / 23,6 ft-lb
Selector de velocidad	Speed knob	Alta - High: 1350 rpm Baja - Low: 400 rpm
Capacidad porta-brocas	Chuck capacity	10 mm
Tiempo de carga	Charging time	300 min
Batería	Battery	20 V/1,5 Ah Litium-ion
Peso llave	Tool weight	1,25 Kg
Peso estuche	Case weight	2,3 Kg
Medidas estuche	Case dimensions	315 x 300 x 100 mm

2 baterías
2 battery

- Selector de potencia - torque adjustment ring
- Embrague 21 posiciones - Clutch 21 sections
- Porta-brocas automático sin llave - Chuck
- Giro reversible - Reversible rotation

US-2040

Estuche de vasos y puntas conexión 1/4" [46 piezas]

Case of wrench sockets & bits, 1/4" connection [46 pieces]



• Peso - Weight: 1,17 Kg

Chrome Vanadium

- ×13 Vasos - Sockets:
4 / 4,5 / 5 / 5,5 / 6 / 7 / 8 / 9 / 10 / 11 / 12 / 13 / 14 mm
- ×21 Vasos con Puntas - Bits Sockets:
— Torx: T10 / T15 / T20 / T25 / T30 / T40
— Hexagonal: 3 / 4 / 5 / 6 / 7 / 8
— Estrella - Phillips: 1 / 2 / 3
— Pozidriv: 1 / 2 / 3
— Plano - Slot: 4 / 5,5 / 7
- ×1 Articulación - Universal Joint
- ×1 Llave Carraca 1/4" - 1/4" Ratchet
- ×1 Maneral "T" corredizo - "T" Sliding Bar (115 mm)
- ×1 Prolongador flexible - Flexible Extension Bar (150 mm)
- ×1 Mango destornillador - Screw handle (150 mm)
- ×1 Adaptador Hexagonal - Hex Adaptor (30 mm)
- ×2 Prolongadores de - Extension Bar (50 mm & 100 mm)
- ×4 Llaves Allen Hexagonales - Allen Key Wrenches (1,27 / 1,5 / 2 / 2,5)

US-1002/2

Lámpara COB LED modelo "HEAD LITE"

Lamp



Fuente luz Light source	4 x SMD LED / Sport 1xSMD LED
Luminous flux, lumen (step 1/2) Spot	75 / 150 75
Illuminance, lux@0,5 m (step 1/2) Spot lux@0,5 m	100 / 200 2000
Illuminance distance	0,50 m
Beam angle	110°
CRI	Ra> 80
CCT	6500K
Adjustable light output	2 Steps
Operating time, (step 1/2) Spot	3 / 1,5 h 3 h
Charging time	2,5 h
Battery	3,7V/800 mAh Li-on
Protection class	IP54
Impact protection	IK07
Impact resistance	1 m
Cable	1m USB
Charging voltage current DC	5V / 1A
Power consumption	Max 1,5 W
Temperature	-10° to +40°C
Dimensions	74x41x41 mm
Net weight	0,073 Kg

EU DESIGNED PATENT